
PE WELDING EQUIPMENT · BUTT FUSION

Ritmo BASIC 355 Butt Fusion Machine

Self-aligning hydraulic butt fusion machine for welding pressure pipes from Ø125 to Ø355 mm, with Ritmo's patented SMARTLock adapter system.

Ø125 – Ø355 MM | 230 V · 5750 W | 8 – 8.5 KVA GEN. | SMARTLOCK



FEATURES

- Self-aligning hydraulic butt fusion machine for pressure pipes carrying water, gas and other fluids
- Built to international standards UNI 10565 and ISO 12176-1
- Machine body with supporting frame, four clamps and two hydraulic cylinders with fast non-drip couplings; SMARTLock fast-locking adapter system, patented by Ritmo
- PTFE-coated heating plate with independent thermometer and "Digital Dragon" high-precision thermoregulator (±1 °C), digital display and LED status indicators
- Extractable electric milling cutter with safety micro-switch and thermal circuit breaker
- Electro-hydraulic gearcase with clamp control lever, maximum pressure and discharge valves (suits "Dual Pressure" welding), non-drip hoses and timer
- Preset for connection to THE INSPECTOR electronic data-logger
- Welds fittings such as elbows, tees, Y-branches and flange necks

STANDARD COMPOSITION


Machine body


Detach device for heater



Gearcase


Heating plate with Digital Dragon


Milling cutter


Support

Also supplied: Inserts Ø4" – 12" IPS; 4" – 12" DIPS, master Ø250 mm · Pre-insulated bag for heating plate · Wooden case for inserts

TECHNICAL FEATURES

Parameter	Value
Working range	Ø125 – Ø355 mm · 4" IPS – 14" IPS
Materials	HDPE, PP, PP-R, PVDF — for other materials contact Ritmo
Power supply	230 V single phase 50/60 Hz
Total absorbed power	5750 W
Suggested power generator	8 – 8.5 kVA
Working temperature	180 – 280 °C (356 – 536 °F)
Outside temperature range	-10 – 40 °C (14 – 104 °F)
Time to reach welding temperature	< 20 min
Dimensions machine body (W × D × H)	1077 × 510 × 715 mm
Weight machine body	100 kg (220.5 lb)
Weight standard composition	205 kg (452 lb)

ON REQUEST

- THE INSPECTOR data-logging
- Trolley
- Tool for flange necks
- Inserts Ø125 – Ø315 mm, master Ø250 mm
- Rollers

The information and photos in this publication are not binding and Ritmo S.p.A. is free to make any alterations without prior notice. Global Water Group — your trusted Ritmo distributor for PE welding solutions.

globalwatergroup.com
sales@globalwatergroup.com
+61 7 3517 5595

LOCATION
36 Hub Crescent, Heathwood QLD 4110 (Head Office)