PE WELDING EQUIPMENT · BUTT FUSION · SEMI-AUTOMATIC

Ritmo DELTA 1000 EASY LIFE Butt Fusion Machine

Self-aligning butt fusion machine for pressure pipes up to Ø1000 mm (36" IPS), with the automated welding process managed by the Easy Life gearcase.

Ø630 – Ø1000 MM | 400 V 3-PHASE · 17200 W | 40 KVA GEN. | WI-FI READY



EASY LIFE SYSTEM

Automated cycle
Operator confirms each phase with a single button; pressure adjustments handled automatically

4,000 welds
Internal data logging with PDF reports downloadable via USB

50 pre-sets
Customisable welding cycles stored on the gearcase

SET & GO PRO
Wi-Fi ready — Android app for setup, GPS, barcodes and reports

FEATURES

- Self-aligning butt fusion machine for pressure pipes carrying water, gas and other fluids; built to UNI 10565 and ISO 12176-1
- Machine body with steel load-bearing frame, four steel clamps and two hydraulic cylinders with non-drip quick couplings and steel inserts
- Self-detaching device assists removal of the heating plate during the welding cycle
- Extractable heating plate with separate thermometer
- Extractable electric milling cutter with safety microswitch and overload protection; metal-framed control box with quick-removal system
- Easy Life electro-hydraulic control unit in an impact- and corrosion-resistant box — repeats welding cycles and controls preset parameters automatically; the operator only confirms each phase
- Wi-Fi ready and compatible with the SET & GO PRO app; graphic display for fast parameter setup
- Data logging of up to 4,000 welds with time stamp; PDF reports exported via USB
- Third clamp fixes to the movable clamps to weld elbows, tees, wyes and stub ends; short-neck stub ends with optional accessory

TECHNICAL FEATURES

Parameter	Value
Working range	Ø630 – Ø1000 mm · 24" – 36" IPS
Materials	HDPE, PP
Power supply	400 V 3F + N + PE 50/60 Hz
Total absorbed power	17200 W
Suggested power generator	40 kVA
Working temperature	180 – 260 °C
Outside temperature range	-10 – 40 °C
Time to reach welding temperature	< 45 min
Pressure range	0 – 250 bar
Memory	4000 welding cycles
Pre-set welding cycles	50 customised
Dimensions machine body (W × D × H)	2386 × 1746 × 1711 mm
Dimensions Easy Life gearcase (W × D × H)	1543 × 600 × 800 mm
Weight machine body	2090 kg
Weight standard arrangement	2939 kg

STANDARD INCLUSIONS


Machine body


Detach device for heater



Easy Life gear case


Facer / Miller


Heating plate


Facer / Heater cradle

OPTIONAL EXTRAS


Inserts Ø 630-900mm


Stub Chuck


Machine Body trolley


Electric Crane


Rollers


App "Set & Go Pro"

SET & GO PRO APP

Wi-Fi control — sends parameters to the machine and manages the welding process

Data collection — scans pipe/fitting barcodes and operator badges, records GPS weld locations, before-and-after photos

Welding reports — PDF reports with graphs, pressures and times; share by email or WhatsApp

Setup — choose ISO, DVS, UNI or ASTM standard, pipe diameter and SDR

Versions — PRO (annual subscription, Google Play) for full connectivity; LIGHT (free) as a parameter calculator

The information and photos in this publication are not binding and Ritmo S.p.A. is free to make any alterations without prior notice. Global Water Group — your trusted Ritmo distributor for PE welding solutions.

globalwatergroup.com
sales@globalwatergroup.com
+61 7 3517 5595

LOCATION
36 Hub Crescent, Heathwood QLD 4110 (Head Office)