PE WELDING EQUIPMENT · DEBEADERS

Ritmo RID Internal Debeader

Removes the internal bead from butt fusion welded pipe Ø90 – Ø630 mm. Intuitive, accurate and versatile — and composed of few parts.

Ø90 – Ø630 MM | SIX HEADS | HDPE · PP · PVDF | FEW PARTS



COMPLETE KIT

- 6 alloy rods, 2.15 m each — one acts as the turn handle
- 5 centre rings keep the rods centred in the pipe
- Rods delivered in a carrying bag with handle
- Debeader heads: 90 – 110, 125 – 160, 160 – 200, 225 – 315 and 355 – 500 mm

SOLD SEPARATELY

- Debeader head 560 – 630 mm

TECHNICAL FEATURES

Head working range	Max bead width
Ø90 – 110 mm	20 mm
Ø125 – 160 mm	25 mm
Ø160 – 200 mm	25 mm
Ø225 – 315 mm	35 mm
Ø355 – 500 mm	35 mm
Ø560 – 630 mm	45 mm

Materials: HDPE, PP, PP-R, PVDF — contact GWG for other materials and the reference chart of SDR covered.



RID removing the internal bead after butt fusion

The information and photos in this publication are not binding and Ritmo S.p.A. is free to make any alterations without prior notice. Global Water Group — your trusted Ritmo distributor for PE welding solutions.

globalwatergroup.com
sales@globalwatergroup.com
+61 7 3517 5595

LOCATION
36 Hub Crescent, Heathwood QLD 4110 (Head Office)